

STINGER S 2000

Basic Equipment Datasheet



DESCRIPTION:

The Stinger is the essential mean to facilitate the cable lay from the deck and grant the correct angle exit, according with the minimum bending radius imposed by cable/umbilical manufacturer.

TECHNICAL DATA

Dimension:

- *Length:* 2.46 m
- *Width:* 1.25 m
- *Height:* 2.30 m

- *Weight:* 1,20 tons

Additional Data:

- *Minimum bending radius:* 2.0 m
- *Max width for cable entrance:* 0.4 m
- *Height (cable entrance):* 0.88 m
- *Bearing Length on the deck:* 1.43 m

STINGER - S 3000

Basic Equipment Datasheet



DESCRIPTION:

The Stinger is the essential mean to ease cable lay from the deck and grant the correct angle exit, according to the minimum bending radius imposed by cable/umbilical manufacturer.

TECHNICAL DATA

Dimension:

- *Length:* 4.70 m
- *Width:* 2.30 m
- *Height:* 4.37 m

- *Weight:* 6,37 tons

Additional Data:

- *Minimum bending radius:* 3.0 m
- *Max width for cable entrance:* 1.0 m
- *Load capacity:* 20 tons max
- *Height (from the deck):* 2.17 m
- *Height (cable entrance):* 1.64 m
- *Bearing Length on the deck:* 2.20 m